



23'-26' X 7' HIGH ALUMINUM SLIDE GATE

(ASG-267) (ASG-BW26)

GATE PART #

BARBWIRE KIT PART #

37'-3"

OPENING

GATE POST SPACING

ALUM TOP TRACK RAIL

2" SQ ALUM UPRIGHT

1" X 2" ALUM BRACING

2" SQ ALUM UPRIGHT

TRUCK ASSEMBLY

4" OD POST

UL 325 COMPLIANT LATCH

HIGH TENSILE WIRE

CHAIN LINK FABRIC

GUIDE ROLLER ASSEMBLY

2" X 4" ALUM BOTTOM RAIL

GATE ELEVATION - SHOWN OSLI, OPENS TO RIGHT
UNIVERSAL DESIGN (CAN BE INSTALLED TO OPEN LEFT OR RIGHT)

Notes.

1. SPECIFICATIONS CAN BE CHANGED BY SHARON FENCE COMPANY ONLY.
2. FOOTING TO BE (4)X POST WIDTH. MIN DEPTH TO BE 36" [914 MM].
3. GATES MAY BE MANUALLY OR ELECTRICALLY OPERATED. HARDWARE WILL VARY.
4. GATES TABULATED ARE UL-325 COMPLIANT.
5. GATES ARE UNIVERSAL (OPEN TO LEFT OR RIGHT).
6. TOP TRACK AND RAIL: ENCLOSED 1-PC ALUMINUM (6061-T6) EXTRUSION (3.83 LBS PER LF) REINFORCED BY WELDING AN ADDITIONAL 2" SQ. ALUMINUM LATERAL SUPPORT RAIL.
7. 1" X 2" ALUMINUM DIAGONAL BRACING WELDED TO 2" SQUARE UPRIGHTS.

| OPENING | GATE POST SPACING |
|---------|-------------------|
| 23' | 14'-0" |
| 24' | 13'-0" |
| 25' | 12'-0" |
| 26' | 11'-0" |

Approved By: _____

Date: _____